



Quad Tracks Now Available From JLG

Not all job sites are created equal and each may pose their own challenges and requirements, including the decision of a tracked or wheeled boom lift. **Quad tracks, now available from JLG**, provide the benefit of both continuous tracks and wheels, giving the operator excellent floatation, minimal rutting at job sites, improved traction, superior comfort over obstacles, and best of all no "break over" effect.

Quad tracks are now available for 600S and 660SJ models and feature:

- Four triangular rubber-track systems that bolt directly to the standard wheel hubs
 - Each system measures 34-in height, 54-in length, 18-in width
- Ability to be swapped for regular tires as needed, or used on other applicable models
- Increased machine utilization and fleet flexibility with quad tracks to handle a variety of job site applications
 - Sand, mud, gravel, grass, paved streets with curbs, potholes, and sharp transitions



Aftermarket Availability

Part Number 1001247800

Fits 600S/660SJ models with serial numbers ranging from:

- US: 0300235168 to present

JLG Industries, Inc.
1 JLG Drive
McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

An Oshkosh Corporation Company

Part No.: Quad Tracks_R1121
Printed in USA

Note: ANSI and CSA only. Requires machine with 2 Wheel Steering. Cannot be outfitted on HC3 models or on machines with 4 Wheel Steering or Tow Bar Package. Additional model applicability coming soon.